



**TÜRK STANDARDLARI ENSTİTÜSÜ**  
**TÜRK STANDARDLARINA UYGUNLUK BELGESİ**  
**TURKISH STANDARDS INSTITUTION**  
**CERTIFICATE OF CONFORMITY TO TURKISH STANDARDS**

Markanın Tanımı Description of the Mark  
TSE veya/or  veya/or T S E

<b>BELGE NUMARASI</b> REFERENCE NUMBER OF LICENCE	001029-TSE-02/04
<b>BELGENİN İLK VERİLİŞ TARİHİ</b> DATE OF FIRST ISSUE OF LICENCE	03.02.2011
<b>BELGENİN SON GEÇERLİLİK TARİHİ</b> LICENCE VALID UNTIL	03.02.2026
<b>BELGE SAHİBİ KURULUŞUN ADI</b> NAME OF THE LICENCE HOLDER	PAKKENS YEDEK PARÇA VE MAKİNA SANAYİ VE TİCARET ANONİM ŞİRKETİ
<b>BELGE SAHİBİ KURULUŞUN ADRESİ</b> ADDRESS OF THE LICENCE HOLDER	MİNARELİÇAVUŞ BURSA OSB MAH. SARI CAD. NO:50 NİLÜFER BURSA/TÜRKİYE
<b>ÜRETİM YERİ ADI</b> NAME OF THE MANUFACTURING PLACE	PAKKENS YEDEK PARÇA VE MAKİNA SANAYİ VE TİCARET ANONİM ŞİRKETİ BURSA VALF ŞUBESİ
<b>ÜRETİM YERİ ADRESİ</b> ADDRESS OF THE MANUFACTURING PLACE	İŞIKTEPEOSB MAH. 75. YIL BUL. NO:15 NİLÜFER BURSA / TÜRKİYE
<b>İPTAL EDİLEN BELGE NUMARASI (Varsa)</b> INDICATION OF SUPERSEDED LICENCE (if any)	001029-TSE-02/03
<b>TESCİLLİ TİCARİ MARKASI</b> REGISTERED TRADE MARK	PAKKENS
<b>İLGİLİ TÜRK STANDARDI</b> RELATED TURKISH STANDARD	TS EN 13547 / 04.01.2016
<b>BELGE KAPSAMI</b> SCOPE OF LICENCE	

BALL VALVE, DN 6, PN 16, VALVE SERIES B, BODY MATERIAL CW 617N, THREADED END (TYPE G),  
MAXIMUM ALLOWABLE TEMPERATURE 80 °C  
BALL VALVE, DN 10, PN 16, VALVE SERIES B, BODY MATERIAL CW 617N, THREADED END (TYPE G),  
MAXIMUM ALLOWABLE TEMPERATURE 80 °C  
BALL VALVE, DN 15, PN 16, VALVE SERIES B, BODY MATERIAL CW 617N, THREADED END (TYPE G),  
MAXIMUM ALLOWABLE TEMPERATURE 80 °C  
BALL VALVE, DN 20, PN 16, VALVE SERIES B, BODY MATERIAL CW 617N, THREADED END (TYPE G),  
MAXIMUM ALLOWABLE TEMPERATURE 80 °C  
BALL VALVE, DN 25, PN 16, VALVE SERIES B, BODY MATERIAL CW 617N, THREADED END (TYPE G),  
MAXIMUM ALLOWABLE TEMPERATURE 80 °C  
BALL VALVE, DN 32, PN 16, VALVE SERIES B, BODY MATERIAL CW 617N, THREADED END (TYPE G),  
MAXIMUM ALLOWABLE TEMPERATURE 80 °C  
BALL VALVE, DN 40, PN 16, VALVE SERIES B, BODY MATERIAL CW 617N, THREADED END (TYPE G),

*e-imzalı/e-signed*

21.01.2025

On Behalf Of The Head Of Certification Center  
BURAK TUNA

TSE BURSA CERTIFICATION MANAGER

\*This certificate also shows that the production place of the certified product meets the requirements of Institute.

\*This certificate under any circumstances cannot be changed, duplicated partially or in a way that makes it difficult to read and erasure cannot be done.

\*TSE \* Address: Organize Sanayi Bölgesi Kırmızı Cad. No:6 16140 BURSA \* Telephone: 02242438000(5H)\* Fax: 02242438324

\*TSE HEAD OF CERTIFICATION CENTER; Address: Necatibey Cad. No:112 06100 Bakanlıklar/ANKARA – Telephone: 0 312 416 64 81 / 416 64 27, Fax:0 312 416 66 17 E-mail :bmb@tse.org.tr , web : www.tse.org.tr





**TÜRK STANDARDLARI ENSTİTÜSÜ**  
**TÜRK STANDARDLARINA UYGUNLUK BELGESİ**  
**TURKISH STANDARDS INSTITUTION**  
**CERTIFICATE OF CONFORMITY TO TURKISH STANDARDS**



(001029-TSE-02/04nolu belge devamı) : PAKKENS YEDEK PARÇA VE MAKİNA SANAYİ VE TİCARET ANONİM ŞİRKETİ  
İLGİLİ TÜRK STANDARDI(RELATED TURKISH STANDARD) TS EN 13547 / 04.01.2016

MAXIMUM ALLOWABLE TEMPERATURE 80 °C  
BALL VALVE, DN 50, PN 16, VALVE SERIES B, BODY MATERIAL CW 617N, THREADED END (TYPE G),  
MAXIMUM ALLOWABLE TEMPERATURE 80 °C  
BALL VALVE, DN 65, PN 16, VALVE SERIES B, BODY MATERIAL CW 617N, THREADED END (TYPE G),  
MAXIMUM ALLOWABLE TEMPERATURE 80 °C  
BALL VALVE, DN 80, PN 16, VALVE SERIES B, BODY MATERIAL CW 617N, THREADED END (TYPE G),  
MAXIMUM ALLOWABLE TEMPERATURE 80 °C  
BALL VALVE, DN 6, PN 25, VALVE SERIES B, BODY MATERIAL CW 617N, THREADED END (TYPE G),  
MAXIMUM ALLOWABLE TEMPERATURE 80 °C  
BALL VALVE, DN 10, PN 25, VALVE SERIES B, BODY MATERIAL CW 617N, THREADED END (TYPE G),  
MAXIMUM ALLOWABLE TEMPERATURE 80 °C  
BALL VALVE, DN 15, PN 25, VALVE SERIES B, BODY MATERIAL CW 617N, THREADED END (TYPE G),  
MAXIMUM ALLOWABLE TEMPERATURE 80 °C  
BALL VALVE, DN 20, PN 25, VALVE SERIES B, BODY MATERIAL CW 617N, THREADED END (TYPE G),  
MAXIMUM ALLOWABLE TEMPERATURE 80 °C  
BALL VALVE, DN 25, PN 25, VALVE SERIES B, BODY MATERIAL CW 617N, THREADED END (TYPE G),  
MAXIMUM ALLOWABLE TEMPERATURE 80 °C  
BALL VALVE, DN 32, PN 25, VALVE SERIES B, BODY MATERIAL CW 617N, THREADED END (TYPE G),  
MAXIMUM ALLOWABLE TEMPERATURE 80 °C  
BALL VALVE, DN 40, PN 25, VALVE SERIES B, BODY MATERIAL CW 617N, THREADED END (TYPE G),  
MAXIMUM ALLOWABLE TEMPERATURE 80 °C  
BALL VALVE, DN 50, PN 25, VALVE SERIES B, BODY MATERIAL CW 617N, THREADED END (TYPE G),  
MAXIMUM ALLOWABLE TEMPERATURE 80 °C

*e-imzalı/e-signed*

21.01.2025

On Behalf Of The Head Of Certification Center  
BURAK TUNA

TSE BURSA CERTIFICATION MANAGER

\*This certificate also shows that the production place of the certified product meets the requirements of Institute.

\*This certificate under any circumstances cannot be changed, duplicated partially or in a way that makes it difficult to read and erasure cannot be done.

\*TSE \* Address: Organize Sanayi Bölgesi Kırmızı Cad. No:6 16140 BURSA \* Telephone: 02242438000(5H)\* Fax: 02242438324

\*TSE HEAD OF CERTIFICATION CENTER; Address: Necatibey Cad. No:112 06100 Bakanlıklar/ANKARA – Telephone: 0 312 416 64 81 / 416 64 27, Fax:0 312 416 66 17 E-mail :bmb@tse.org.tr , web : www.tse.org.tr

